

1 Products affected

Product hierarchy no. *				Part no.	SBU	Type / Description	Customer part no.
SBU	PG	PGU	Type				
02	007	012	0000001400	6610	Connectors	Appliance Outlet	6610.XXXX.XX

*SBU (2-digit) / PG (3-digit) / PGU (3-digit) / Type (10-digit)

2 Type of change

Change of maximum applicable wire diameter (with insulation).

3 Detailed description of change

The Data sheet and the mounting instruction prescribed a maximum diameter of insulated wires of 3.3mm. To give the chance to use standard insulated wires the diameter is enlarged to 3.6mm for arrangement along, respective 3.5mm for arrangement cross.

There is no change on the Product.

4 Reason of change

The standard solid wires have a range of 3.2mm-3.9mm (metric standard) and 2.3mm-3.6mm (AWG standard).

To give the chance to use a range of the metric standard the wire diameter is raised up to 3.6mm.

5 Released date

Release for series production

WW12/2012

6 Impact of change and recommended action

Form: N/A
Fit: New wire range usable for customer
Function: Standard wires usable for customer
Production Site: N/A

7 Reference Documents / Attachments

Kind of document	Document number	Remarks
Data sheet	0105.1973	
Mounting instruction	0105.1973_4.5	

6610					0118.2100	
creation date	created by	release date	released by	notification no.	revision	page
2012-03-23	sha	2012-03-23	sha	23169		1 of 1