Socket, PCB terminals, insulated, 3.5 mm, 3-pole, straight, UK-Connector



See below:

## **Approvals and Compliances**

# **Description**

- PCB :
  - Screw-on mounting, rear-side
- Data and Signal transfer
- Data and Signal Connectors 3-pole , insulated , straight
- Reinforced gold plating for increased insertions

#### **Characteristics**

- Does not comply with the JAP or BPO standard

#### References

Alternative: Housing shielded 4802.2320

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product

Technical Data	
Diameter	3.5 mm
Number of Poles	3-pole
Ratings DC	1 A / 12 VDC
Ratings AC	1 A / 12 VAC
Dielectric Strength	500 VDC
Insulation Resistance	> 10000 MΩ @ 500 VDC

Allowable Operation Tempe-	-20°C to 70°C	
rature		
Terminal	PCB terminals	
Mounting	Screw-on mounting wall thickness max. 2.0 mm	
Housing	insulated	
Style	straight	
Lifetime	10000 Insertions	

# **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
50	China RoHS	SCHURTER AG	The law SJ $/T$ 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

## Dimensions [mm]



# **Diagrams**



## **All Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/ Sockets	3.5	3-pole	PCB terminals	4802.2330

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/support-tools/stock-check-distributors

Packaging unit 100 Pcs

## Mating Inlets/Plugs

Category / Description



Data and Signal Plug/Socket Overview complete

Plug, solder terminal, screened, 3.5 mm, 3-pole, straight, UK-Connector 4802.1300
Plug, solder terminal, insulated, 3.5 mm, 3-pole, straight, UK-Connector 4802.1310