Fuse DTIII 500V



See below:

Approvals and Compliances

Description

- Operation full range cable defensive fuses
- Over-load and short-circuit protection
- Colored characteristic detector in the middle
- Characteristic gG
- According to IEC 269

Technical Data

Rated Current In	32- 63A
Rated Voltage	500 VAC
Breaking Capacity	50kA
Rated Power Operating Fre-	50Hz
quency fe	

Basic Design		
Insulator	Ceramics	
Metal components	Brass	

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Time-Current-Curves

DT II - DT III



Current in Amperes

All Variants

Rated current	Color	Packaging unit	Order Number	E-No.	
[A]		Pcs			
32	black	25	0001.2066	800353009	
35	black	25	0001.2028	800353509	
40	black	25	0001.2029	800354009	
50	white	25	0001.2030	800355009	
63	copper	25	0001.2031	800356009	

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

other products